



# GPSdome-LightHouse

The industry's most disruptive, future-proof, GNSS Anti Jamming Solution

OtoSphere-LightHouse\* is a compact, rugged, and cost-effective GNSS anti-jamming module, designed to ensure continuous navigation and autonomous operation in environments affected by GNSS interference.

Equipped with advanced, field-upgradeable anti-jamming algorithms and real-time monitoring capabilities, LightHouse delivers robust protection against both current and emerging GNSS threats. Optimized for commercial ground, aerial, and maritime platforms, its compact and lightweight form factor enables easy integration providing high-end GNSS resilience without compromise.

*\*Designed for non-military platforms and applications.*



## Unique advantages

- **Software-defined**  
Upgradeable anti jamming algorithms
- **Wide receiver compatibility**  
Works with legacy and modern GNSS receivers
- **Configurable protection**  
1 or 2 protected GNSS bands
- **Passthrough support**  
Optional 1 or 2 unprotected GNSS bands
- **Low power**  
3W average consumption
- **Low latency**  
Group delay < 100ns
- **Optimized design**  
Compact, lightweight, and efficient
- **Jamming detection**  
Real-time jamming status, power levels



## Product Dimensions

	Type	Weight	Size
Enclosed	Single Band	180g (6.35oz)	80x78.5x28 mm 3.15x3.09x1.10 in
	Dual Band	200g (7.05oz)	80x78.5x33.5 mm 3.15x3.09x1.32 in
OEM	Single Band	80g (2.82oz)	76x55x22.2 mm 2.99x2.17x0.87 in
	Dual Band	100g (3.53oz)	76x55x30.8 mm 2.99x2.17x1.21 in

Mounting: 4 x M3 screw (not supplied).

## Performance

<b>Protected Frequency*</b>	Single Band L1/E1, L2, L5, G1 Optional Secondary Band: L1/E1, L2, L5, G1
<b>Passthrough</b>	Optional L1/E1, L2, L5, G1
<b>Latency</b>	> 100ns
<b>Compression Point</b>	-23dBm
<b>Path Gain</b>	+/- 3dB

\*Does not support M-Code and SAASM.

## LED Indicator

<b>Flashing Green</b>	Standby mode, Bypass mode
<b>Green</b>	Stop mode (Service)
<b>Flashing Green/Orange</b>	System active, jamming detected
<b>Flashing Orange</b>	High power Jamming detected
<b>Red</b>	Error state

## RF Interfaces

	Connector	Description
<b>Antennas Input</b>	A1,A2	50Ω SMA 2.7-14VDC, Max 40mA per connector, 15dB -40dB gain
<b>Receiver Output</b>	RX1	50Ω SMA
	RX2*	50Ω SMA

\*Not protected - For secondary receiver/hearing calculations.

## Wire Connection Description

<b>power Supply</b>	6-32 VDC	Positive (+)	Red
	Avg ~ 3W**	GND (-)	Black
<b>Dry Contacts</b>	Jamming indication	Positive	Purple
	Max 32V 50mA	Negative	Green
<b>UART*</b>	Status and Maintenance	UART RX	Gray
		UART TX	Yellow
		VCC 5v+	White
		GND	Blue

\* No Built-in GNSS receiver.

\*\* For Single Band version.

## Environmental


<b>Operating Temperature</b>	-40°C to 71°C
	-40°F to 159.8°F
<b>IP Rating</b>	<b>Enclosed</b> IP65
	<b>OEM</b> NO

## Safety & Compliance


FCC Compliant | CE Compliant | RoHS Compliant

## Product Dimensions

### Enclosed



### OEM



## Ordering Information

OtoSphere-LightHouse — X — X — X — X — X

Protected frequency	Type	Passthrough frequency*	Second Receiver**
1 - GPS L1/GALILEO E1 2 - GPS L2 3 - GPS L5 4 - GLONASS G1	E - Enclosed O - OEM	0 - null 1 - GPS L1/GALILEO E1 2 - GPS L2 3 - GPS L5 4 - GLONASS G1	1 - Yes 2 - No
		*Does not support M-Code   SAASM	** Not Protected

Version 1.0.4



**infiniDome, Ltd**

7 Ha'eshel St. Industrial Park (South), P.O. Box 3358, Caesarea 3079504, Israel

info@infinidome.com • www.infinidome.com